



Carousel[™] Stirring Hotplates





Powerful stirring and fast heating with a chemically-resistant top plate and built-in safety features



Carousel Core+ and Heat-On 500 ml block



Carousel Core+ and Carousel 6 Plus Reaction Station



Carousel Core+ Hotplate, Pt1000 with holder and Heat-On block

Carousel Core+ Stirring Hotplate

800 Watt heating power with a chemically resistant top plate

Features include

- Hotplate temperature range: 20 to 300 °C.
- Speed range 100 to 1400 rpm.
- Digital display of temperature and speed with both set and actual values.
- Temperature and rotation knobs can be locked to prevent changing of set values.

Faster heating

- 800 Watt heating power heats rapidly.
- Reduces heat-up times by 35%.

Kera-Disk® top plate

- · Rapid heat transfer for fast heating.
- · Chemical and scratch resistant.
- 135 mm diameter.

Stirring control

- · Powerful and even stirring.
- Smooth ramp to set speed which prevents decoupling of magnet.

Pt1000 temperature sensor


- For precise control by solution or block temperature.
- Accuracy with sensor ±1 K.

Safety features

Carousel Core+ Stirring Hotplate provides built-in safety features as standard to protect both the user and the sample.

Sealed housing

Sealed against solvent and vapour for long lifetime.









Superior safety features

- Separate on/off switch for heating prevents unintentional heat-up.
- When heating is switched on, the on/off button is illuminated for visual control.
- Residual heat indicator provides a clear warning if top plate surface is greater than 50 °C, minimising accidental burns.
- An independent safety circuit switches off the heating if the set hotplate temperature is exceeded by 25 °C.
- To protect your sample from overheating a safety circuit switches off the heating if temperature sensor is not immersed in the medium.
- · Stirring control features a smooth ramp to set speed which prevents decoupling.

Technical specification

| Model | Carousel Core+ Stirring Hotplate |
|--|--|
| Dimensions (W × H × D) | 168 × 101 × 299 mm |
| Usable surface top plate | Ø 135 mm |
| Weight approx. | 3 kg |
| Maximum permissible load | 25 kg |
| Drive | EC motor, left-turning |
| Speed range | 100 – 1,400 rpm |
| Adjustment accuracy | 5 rpm |
| Heating power | 800 W at 230 V (EU) 600 W at 115 V (US) |
| Heating temperature range | 20 – 300 °C |
| Heating control | PID |
| Adjustment accuracy | ±1 K |
| Measurement accuracy (DIN IEC 751 Class a) | ± 0.2 K, plus tolerance Pt1000 |
| Measurement resolution | ± 1 K |
| Display | LCD display |
| Protection class | (EN 60529) IP42 |
| Acoustic pressure | < 50 db(A) |



Carousel Core+ has a connection for an external Pt1000 temperature probe

Findenser[™]- requires no running water to operate

Replaces the need for water-cooled condensers in over 95% of all common chemistry applications, whilst minimising the risk of flooding in the laboratory

Benefits

- · No risk of flooding from running water.
- Eliminates water purchase and disposal costs.
- Suitable for solvent volumes from 5 ml up to 1 litre.
- · Helps meet sustainable water reduction targets.
- · A finned aluminium jacket to ensure hgh performance air-cooling.
- A patented design to encapsulate thermofluid for maximised thermal conductivity and heat transfer.





Pt1000 Temperature Sensors and Accessories



Pt1000 S/S




Rod Supprt Hotplate
Adapter (extension plate)



Pt1000 Clamping System + Support Rod and Cable Guide



Temperature Sensor



RR71125 Support Rod (13 mm x 340 mm) RR91229 Support Rod (13 mm x 425 mm)

Support Rod (13mm x 500 mm)

RR91230 Support Rod for 4 L Heating Bath

Hotplate Accessories



5 litre Heating Bath Liquid up to 220°C



RR91238 Silicone Protective Cover



Boss Head



Retort Clamp to 85 mm



RR91220 1 litre PTFE Coated Heating Bath



RR91221 2 litre PTFE Coated Heating Bath



RR91222 4 litre PTFE Coated Heating Bath



Holding Bracket & Clamp



1 litre Heating Bath 2 litre Heating Bath



4 litre Heating Bath



145 mm Adanter Plate

High Performance PTFE Stirring Bars



10 mm Cross Shape

RR98091 16.5 mm RE Cross Shane

15 mm Pivot Ring



30 mm Cross Shape



10 mm RE Elliptical

12 mm RE Cylindrical

15 mm RE Ellintical



40 mm

Oval Shane



Elliptical



50 mm



PTFE Magnetic Stir Bar Evaluation Kit



8 mm Cylindrical

PTFE Magnetic Stir Bar Evaluation Kit - For Flask



13 mm

PTFE Magnetic Stirring Bar Retriever



Stirring Bar

Carousel Core+ Stirring Hotplate 230v

Carousel Core+ Stirring Hotplate 230v UK Plug RR91213 RR91213/EURO Carousel Core+ Stirring Hotplate 230v Euro Plug RR91213/SWISS Carousel Core+ Stirring Hotplate 230v Swiss Plug RR91213/USA Carousel Core+ Stirring Hotplate 230v US Plug

Carousel Core+ Stirring Hotplate + PT1000

Carousel Core+ Stirring Hotplate + PT1000 230v UK Plua RR91216 Carousel Core+ Stirring Hotplate + PT1000 230v Euro Plug
Carousel Core+ Stirring Hotplate + PT1000 230v Euro Plug
Carousel Core+ Stirring Hotplate + PT1000 230v Swiss Plug RR91216/EURO RR91216/SWISS Carousel Core+ Stirring Hotplate + PT1000 230v US Plug RR91216/USA

Carousel Core+ Stirring Hotplate Package 230v

RR91292 Carousel Core+ Stirring Hotplate Package 230v UK Plug RR91292/EURO Carousel Core+ Stirring Hotplate Package 230v Euro Plug RR91292/SWISS Carousel Core+ Stirring Hotplate Package 230v Swiss Plug RR91292/USA Carousel Core+ Stirring Hotplate Package 230v US Plug

Consisting of the following:

RR91213 Carousel Core+ Stirring Hotplate Pt1000 S/Steel Temperature Sensor RR91226

Pt1000 Clamping System - Support Rod and Cable Guide RR91235

RR91238 Silicone Protective Cover

Pt1000 Temperature Sensors and Accessories

RR91226 Pt1000 S/S Temperature Sensor RR91227 Pt1000 Glass Coated Sensor

RR71120 Support Rod Hotplate Adapter (extension plate)

Pt1000 Clamping System + Support Rod and Cable Guide RR91235 Pt1000 Clamping System + Support Rod and Cable Guide (bath from 3 to 5 L) RR91236

RR91228 Temperature Sensor Holder RR71125 Support Rod (13 mm x 340 mm) RR91229 Support Rod (13 mm x 425 mm) RR71127 Support Rod (13 mm x 500 mm)

RR91230 Support Rod for 4 litre Heating Bath (13 mm x 475 mm)

Hotplate Accessories

RR91225

569-00600-00 5 litre Heating Bath Liquid up to 220°C Silicone Protective Cover RR91238

RR71115 Boss Head 16 mm RR71110 Retort Clamp to 85 mm RR91220 1 litre PTFE Coated Heating Bath 2 litre PTFE Coated Heating Bath RR91221 RR91222 4 litre PTFE Coated Heating Bath RR91232 Holding Bracket & Clamp RR91223 1 litre Heating Bath RR91224 2 litre Heating Bath

4 litre Heating Bath RR91238 Silicone Protective Cover for Core+ Hotplate RR61085 145 mm Adapter Plate for 135 mm Hotplates

High Performance PTFE Stirring Bars

RR98075 Cross Shape Stirring Bar 10 mm, pk 40 RR98091 Cross Shape Stirring Bar 16.5 mm Rare Earth, pk 20 RR95910 Cross Shape Stirring Bar 30 mm, pk 5 RR98096 Elliptical Stirring Bar 10 mm Rare Earth, pk 40 RR98097 Elliptical Stirring Bar 15 mm Rare Earth, pk 20 Elliptical Stirring Bar 25 mm Rare Earth, pk 10 RR99064 RR99607 Pivot Ring Stirring Bar 12 x 4.5 mm, pk 40 Pivot Ring Stirring Bar 12 x 6 mm, pk 40 RR98071 RR99613 Pivot Ring Stirring Bar 15 mm, pk 40 RR95905 Cylindrical Stirring Bar 8 mm, pk 40 Cylindrical Stirring Bar 12 mm Rare Earth, pk 20 RR98113

RR98070 Octagonal Stirring Bar 13 mm, pk 20

RR95920 Oval Stirring Bar 40 mm, pk 5 RR95921 Oval Stirring Bar 50 mm, pk 5

RR98095 PTFE Magnetic Stir Bar Evaluation Kit, pk 30 RR71200 PTFE Magnetic Stir Bar Evaluation Kit - for flasks, pk 10

RR98094 PTFE Magnetic Stir Bar Retriever 350 mm

RR98114 Stirring Bar Restrainer

Radleys provide innovative chemistry equipment for safer, cleaner, greener and more productive chemical research.

Visit www.radleys.com to see our full range of chemistry productivity tools.

